

5

## CLAIMS

What is claimed is:

1. A method of automatically controlling the exposure time and gain of an image  
10 sensor, said image sensor including a matrix of pixels, said method comprising:

determining if a first image provided by said image sensor has an overall brightness that  
falls within a stable range;

if said brightness of said first image falls within said stable range, maintaining the  
exposure time and gain of said image sensor for capture of a subsequent second image;

15 if said brightness of said first image falls outside of said stable range, then adjusting said  
exposure time downward by a first predetermined increment if said brightness is higher than said  
stable range, else adjusting said exposure time upward by a second predetermined increment if  
said brightness is lower than said stable range; and

20 determining if said adjustment of exposure time downward or upward is greater than a  
predetermined threshold, and if so, increasing said gain of said image sensor if said exposure  
time is adjusted downward, else decreasing said gain of said image sensor if said exposure time  
is adjusted upward.

2. The method of Claim 1 wherein said predetermined threshold is substantially a  
25 magnitude of said stable range.

3. The method of Claim 1 wherein said exposure time is measured as an exposure  
row count.

5           4.     The method of Claim 3 wherein said first predetermined increment and said second predetermined increment is one row.

          5.     The method of Claim 1 wherein the amount of increase of said gain is dependent upon the percentage decrease of exposure time and the amount of decrease of said gain is  
10    dependent upon the percentage increase of exposure time.

          6.     An image sensor that includes a matrix of pixels and an adjustable exposure time and gain, the image sensor comprising:

              means for determining if a first image provided by said image sensor has an overall  
15    brightness that falls within a stable range;

              means for if said brightness of said first image falls within said stable range, maintaining the exposure time and gain of said image sensor for capture of a subsequent second image;

              means for if said brightness of said first image falls outside of said stable range, then  
20    adjusting said exposure time downward by a first predetermined increment if said brightness is higher than said stable range, else adjusting said exposure time upward by a second predetermined increment if said brightness is lower than said stable range; and

              means for determining if said adjustment of exposure time downward or upward is greater than a predetermined threshold, and if so, increasing said gain of said image sensor if said exposure time is adjusted downward, else decreasing said gain of said image sensor if said  
25    exposure time is adjusted upward.

5           7.     The image sensor of Claim 6 wherein said predetermined threshold is substantially a magnitude of said stable range.

          8.     The image sensor of Claim 6 wherein said exposure time is measured as an exposure row count.

10

          9.     The image sensor of Claim 8 wherein said first predetermined increment and said second predetermined increment is one row.

15           10.    The image sensor of Claim 6 wherein the amount of increase of said gain is dependent upon the percentage decrease of exposure time and the amount of decrease of said gain is dependent upon the percentage increase of exposure time.